### REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed; and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this is not to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the

1. AGENCY USE ONLY (Leave blank)

2. REPC DATE 03/01/91 3. REPORT TYPE AND DATES COVERED POP Test (12/90)

4. TITLE AND SUBTITLE

Performance Oriented Packaging Testing of Mk 592 Mod 0 Container

5. FUNDING NUMBERS

6. AUTHOR(S)

Eric Wu

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

Naval Weapons Station Earle Colts Neck, NJ 07722-5000

8. PERFORMING ORGANIZATION REPORT NUMBER

DODPOPHM/USA/DOD NADTR91002

9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)

Naval Air Systems Command Washington, DC 20361-0001

10. SPONSORING / MONITORING AGENCY REPORT NUMBER


Same as above

11. SUPPLEMENTARY NOTES

N/A

12a. DISTRIBUTION / AVAILABILITY STATEMENT

This document has been approved for public release and sale; its distribution is unlimited.



DISTRIBUTION CODE

### 13. ABSTRACT (Maximum 200 words)

Qualification tests were performed to determine whether the in-service Mk 592 Mod 0 Shipping and Storage Container could be utilized to contain properly dunnaged solid type nazardous materials weighing up to a gross weight of 215 kg (474 pounds). The tests were conducted in accordance with Performance Oriented Packaging (POP) requirements specified by the United Nations Recommendations on the Transportation of Dangerous Goods and the Department of Transportation's Title 49 CFR and the Final Rulings published in the Federal Register, Vol. 55 on 21 Dec 90. The container has conformed to the POP performance requirements; i.e., the container successfully retained its contents throughout the specified tests.

72000	2.	•	
6		i i	
			: \ :

14. SUBJECT TERMS	15. NUMBER OF PAGES		
POP Test of Mk 592	6		
:			16. PRICE CODE
13 CECHAITY CLACECICATION	TAR CECURITY CLASSICATION	19. SECURITY CLASSIFICATION	20. LIMITATION OF ABSTRACT
17. SECURITY CLASSIFICATION OF REPORT	OF THIS PAGE	OF ABSTRACT	20. CIMITATION OF ABSTRACT
UNCLASSIFIED	UL	1 UL	UL.

### **GENERAL INSTRUCTIONS FOR COMPLETING SF 298**

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the less of the report, particularly the cover and title page, instructions for filling in each block of the form follow. It is important to stay within the lines to meet optical scanning requirements.

- Block 1. Agency Use Only (Leave blank).
- Block 2. Report Date. Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least the year.
- Block 3. Type of Report and Dates Covered State whether report is interim, final, etc. It applicable, enter inclusive report dates (e.g. 10 Jun 87 30 Jun 88).
- Block 4. <u>Title and Subtitle</u>. A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.
- Block 5. Funding Numbers. To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

C - Contract G - Grant PE - Program

Element

TA - Task
WU Work Unit
Accession No

PR - Project

- Block 6. Author(s). Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).
- **Block 7.** Performing Organization Name(s) and Address(es). Self-explanatory
- **3lock 8.** Performing Organization Report Member Enter the Inique alphanisment report number(s) assigned by the organization performing the report.
- **Block 9.** <u>Toonsoring/Monitoring when a Namerst</u> and Addressless Seithers assured.
- Block 10. Donsor-eq. Man Sor eq. Authory. Report Number of Rhows
- Block 11. Supplementary loces Interinformation not included eisewhere such as.

  Prepared in cooperation with the frank of the Tolbe of Statement whether the new report supersedes or supplements the older in port.

Block 12a. <u>Distribution/Availability Statement.</u>
Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR).

DOD - See DoDD 5230.24, "Distribution Statements on Technical Documents."

**DOE** See authorities.

NASA - See Handbook NHB 2200.2.

NTIS - Leave blank.

Block 12b. Distribution Code.

DOD - Leave blank.

DOE - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports.

NASA - Leave blank.
NTIS - Leave blank.

- Block 13. Abstract. Include a brief (Maximum 200 words) factual summary of the most significant information contained in the report.
  - **Block 14.** <u>Subject Terms.</u> Seywords or phrases dentitying major subjects in the report.
- , Block 15. <u>Sumper of Pages</u>. Enter the total number of nages
  - Slock 16. <u>AncarCyde</u>. Enter labrophiste price lage (ATTS Liniv)
  - Blocks 19 13. Security Class Flutions Belfexcellenter, Finter B.S. Security Classification in Coculone with 10 Security Requiations tile, 10 Assistant Intermitation on the top and office of the base
  - alock 26. <u>Imitation of Abstract</u> This block must be completed to assign a limitation to the abstract. Inter either 15 (i), himited or SAR (same is report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unimited.

### DODPOPHM/USA/DOD/NADTR91002

### PERFORMANCE ORIENTED PACKAGING TESTING OF MK 592 MOD 0 CONTAINER

Author: Eric Wu Mechanical Engineer

Performing Activity: Naval Weapons Station Earle Colts Neck, New Jersey 07722-5000

1 March 1991

## ccesion For ITIS CRA&I TIC TAB Inarincenced Justification y intribution/ Availability Codes ist Avail and/or Special

### FINAL

DISTRIBUTION UNLIMITED

Sponsoring Organization: Naval Air Systems Command Code AIR-41821A Washington, DC 20361-0001

### INTRODUCTION

The Mk 592 Mod 0 Container, which contained 474 pounds of inert HARPOON Warhead, had an overall weight of 717 pounds. This Performance Oriented Packaging (POP) test was performed to ascertain whether this standard container (Packing Group II) would meet the requirements as specified by the United Nations Recommendation on the Transportation of Dangerous Goods Document, ST/SG/AC.10/1, Revision 6, Chapters 4 and 9. A base level vibration test per the Department of Transportations 49 CFR Final Rulings (Federal Register, Vol. 55, No. 246) on Performance Oriented Packaging was previously conducted by WPNSTA Earle. This is documented in NWHC Report 7676. Due to unavailability, the number of containers used was less than the number required by the UN Recommendation. This has been approved by The Under Secretary of Defense, Memorandum for the Joint Logistics Commanders dated 22 February 1990.

The objective of these tests was to ensure that the sample container could withstand conditions of transportation outlined by the UN requirements. The test is representative of the worse case loading of the Mk 592 Mod 0 Container.

### **TESTS PERFORMED**

### 1. Stacking Test

This test was performed in accordance with ST/SG/AC.10/1, chapter 9, paragraph 9.7.6. One container was used for this test. The container was subjected to a force applied to its top surface equivalent to the total weight of identical packages stacked to a height of 3 meters (including the test sample). A stacked weight of 2,151 pounds was used for this test. The test was performed for 24 hours. After the allowed time, the weight was removed and the containers examined.

### 2. Dron Test

This test was performed in accordance with ST/SG/AC.10/1, chapter 9, paragraph 9.7.3. One container was used throughout the test. The drops were performed from a height of 4 feet impacting the following surfaces:

- a. Flat bottom
- 5. Flat top
- c. Flat on long side
- d. Flat on short side
- e. One corner

This test was performed at animient temperature of  $\pm 10 \pm 20$  °F.

### PASS/FAIL (UN CRITERIA)

### 1. Stacking Test (UN CRITERIA)

The criteria for passing the stacking test is outlined in paragraph 9.7.6.3 of ST/SG/AC.10/1 and states the following: "... no test sample should leak. No test sample should show any deterioration which could adversely affect transport safety or any distortion liable to reduce its strength or cause instability in stacks of packages."

### 2. Drop Test (UN CRITERIA)

The criteria for passing the drop test is outlined in paragraph 9.7.3.5 of ST/SG/AC.10/1 and states the following: "Where a packaging for solids undergoes a drop test and its upper face strikes the target, the test sample passes the test if the entire contents are retailed by an inner packaging or inner receptacle; e.g., a plastic bag, even if the closure is no longer sift-proof. A slight discharge from the closure(s) upon impact should not be considered to be a failure of the packaging provided that no further leakage occurs."

### TEST RESULTS

### 1. Stacking Test

Satisfactory.

### 2. Drop Test

Satisfactory.

### DISCUSSION

### 1. Stacking Test

The container was visibly checked after the 24-hour period was over. There was no leakage, distortion, or deterioration to any of the containers as a result of this test.

### 2. Drop Test

After each drop, the containers were inspected for any damage which would be a cause for rejection. Final inspection indicated damage was infinitely with only minor denting noted. The port side skid broke apart after the corner drop (fwd-port corner); however, no leakage was found. The container remained intact and serviceable on completion of the tests.

### REFERENCE MATERIAL

- A. United Nation's "Recommendation on the Transportation of Dangerous Goods," ST/SG/AC.10/1, Revision 6
- B. NWHC Report 7676, 30 September 1976, Test and Evaluation of Prototype Container, Mk 592 Mod 0, for HARPOON Warhead and Exercise Sections
- C. Performance Oriented Packaging Standards; Changes to Classification, Hazard Communication, Packaging and Handling Requirements Based on UN Standards and Agency Initiatives; Final Rule, Federal Register, Vol. 55, No. 246 of December 21, 1990

### **DISTRIBUTION LIST**

Defense Technical Information Center (2 copies) ATTN: DTIC/FDA Bldg. 5, Cameron Station Alexandria, VA 22304-6145

Headquarters, Military Traffic Management Command (2 copies) ATTN: T-SS, James Gibson 5611 Columbia Pike Falls Church, VA 22041-5050

### TEST DATA SHEET

DATA SHRET: Container: Mk 592 Mod 0 Container Type: 4B1 Container P/N or NSN: NSN 8140-01-087-6689 Material: Specification Number: DL 2643225 Aluminum Capacity: Dimensions: 325.2 kg (717 pounds) 57.25" L x 28.75" W x 30.25" H Closure (Method/Type): Tare Weight: Removable Cover 99.8 kg (220 pounds) Additional Description: PRODUCT: See table Name: See table NSN(s): See table United Nations Number: See table United Nations Packing Group: II Physical State (Solid, Liquid, or Gas): Solid At 50 °C: N/A Vapor Pressure (Liquias Only): N/A At 55 °C: N/A Consistency/Viscosity: Y/A Density/Specific Gravity: N/A Amount Per Container: See table Flash Point: N/A Net Weight: See table TEST PRODUCT: Inert HARPOON Warhead Name: Simulated Weight Physical State: Solid Consistency: N/A Density/Specific Gravity: N/A Test Pressure (Liquids Only): N/A

Gross Weight: 215 kg (474 pounds)

Amount Per Container: 1

TABLE

NALC	NSN	Туре	Packing Drawing	UN Code	UN Number	#/ Cntr	Weight (kg)
9 <b>u</b> 68	1336-01-201-3933	Exercise Section	2643225	1.45	0173	1	222.26
9 <b>469</b>	1336-01-202-4531	Exercise Section	2643225	1.45	0173	1	222.26
9w70	1336-01-201-3937	Exercise Section	2643225	1.45	0173	1	222.26
V540	1336-01-110-5581	Warhead Section	2643225	1.10	0286	1	213.19
V555	1336-01-146-7664	Warhead Section	2643225	1.10	0286	1	225.44
V556	1336-01-146-7665	Warhead Section	2643225	1.10	0286	1	225.44
v558	1336-01-186-5966	Warhead Section	2643225	1.1D	0286	1	222.26
v559	1336-01-186-5967	Warhead Section	2643225	1.10	0286	1	222.26
v550	1336-01-269-1698	Warhead Section	· 2643225	1.10	0286	1	222.26

### MK 592 MOD 0 CONTAINER POP MARKING

# UN 4B2/Y325/S/90/USA/DOD/NAD